

ABRO FLUORESCENT SPRAY PAINT

ABRO Fluorescent Spray Paint is a versatile all-purpose, fast drying spray paint useful for exterior and/or interior application to many surface types for a fast dry bright finish.

APPLICATIONS

*May be used on wood, metal, drywall, plaster, cardboard, and masonry.

Examples as follows:

- Furniture
- Toys
- Lamps
- Cabinets
- Bicycles
- Doors
- etc.

All surfaces must be free of any grease, dirt, rust, moisture, loose paint, or any other material which might interfere with proper adhesion. Glossy surfaces must be dulled by light sanding. Metals should be rust free and primer should be used for best results.

Fluorescent colors available in Green, Red, Orange, Yellow, Blue, and Pink.

DIRECTIONS

- 1) Protect surrounding areas from spray mist with a drop cloth or newspapers.
- 2) For best results, use only when can temperature is between 70°F and 90°F.
- 3) Shake can vigorously for at least one minute after mixing ball rattles to ensure color uniformity and prevent clogging.
- 4) Press spray button firmly and use steady even strokes while spraying – several thin coats gives a better finish than one heavy coat.
- 5) Important: Follow instructions on can in the case of a clog. Do not stick pin or other object into can.

DRY TO TOUCH: 10-15 minutes

DRY TO HANDLE: 20-30 minutes

(continue)

PACKAGING AND STORAGE

- 16-ounce metal aerosol can / 12 cans per case
- Store below 90°F, preferably at 70°F
- Shelf life is 12 months minimum from the date of manufacture when subject to storage requirements
- Keep away from heat, sparks and open flame – do not expose to temperatures above 120°F

TECHNICAL DATA

Appearance and Odor	Aerosol Product
Cautions	Contents Under Pressure. Extremely Flammable!! Skin, Eye and Nose Irritant. Use With Adequate Ventilation. Non-Toxic When Dry.
Specific Gravity (H ₂ O=1)	0.71
Boiling Range	-13°F – 280°F
Solubility in Water	NIL
Evaporation Rate	Faster Than Ether
Coating V.O.C.	4.66 lb. / gal. (558 G/L)
Flash Point	-40°F
Flammable Limits In Air by Volume	Lower 0.7% Upper 9.5%
Hazardous Ingredients	Xylene (Mixed Isomers), Toluene, Acetone

Since 1939 A Trusted Name Worldwide