



HP Lubricants - Product Data Sheet



HP GEAR OIL EP 80W , 90,140

- HP GEAR OIL EP ARE MULTIPURPOSE GEAR OILS CONTAINING EXTREME PRESSURE ADDITIVES FOR MODERATE SERVICE CONDITIONS
- MEETS API GL-4, MIL-L-2105 & EP TYPE GL-4 LEVEL OF IS:1118:1992 SPECIFICATIONS
- APPLICATION AREAS ARE MANUAL TRANSMISSIONS OF AUTOMOBILES REQUIRING THIS TYPE OF EXTREME PRESSURE OILS
 - EXCELLENT THERMAL & CHEMICAL STABILITY
 - PROTECTION AGAINST RUST AND CORROSION ENSURING LONGER TROUBLE FREE PROTECTION

	80w	90	140
KINEMATIC VISCOSITY <i>est @ 100 C</i>	11-12.3	14.5-17.3	28-33
VISCOSITY INDEX,MIN	90	90	90
FLASH POINT, (COC) C,MIN	165	180	190
POUR POINT, C , MAX	-27	-9	-3
CORROSION COPPER STRIP			
AT 121 C FOR 3 HRS MAX.	2	2	2

APPROVED BY:

M/s VOLTAS LTD.,M/s BEML , M/s TELCO
 M/s HMT , M.s ASHOK LEYLAND, M/s PUNJAB TRACTORS
 M/s HINDUSTAN MOTORS, M/s EICHER M/s ECEL,M/s ESCPRTS
 M/s BAJAJ TEMPO