



Tractor Acrylic Distemper

DA

**Product Description**

Asian Paints Tractor Acrylic Distemper is a water-based, interior wall paint. It is India's best and most trusted distemper and gives walls a delightful, attractive, matt finish that lasts for ages.

**Performance Features & Benefits**

Asian Paints Tractor Acrylic Distemper gives unmatched durability and a smooth finish that has no equal in the distemper category. It is a time-tested formulation with acrylic copolymer binder that gives it this unparalleled performance. Its special formulation ensures shade retention for a long time and its fast drying property facilitates quicker completion of painting jobs. It is available in a unique range of 450 bright, attractive shades that have excellent cleanliness.

**Recommended Usage**

Asian Paints Tractor Acrylic Distemper can be applied on all types of plasters, false ceiling, asbestos sheets, concrete etc. It is designed for interiors.

**Recommended Application**

Apply topcoats of Tractor Acrylic Distemper as follows :

Product	Product Code	Thinner	Dilution % (by vol)	Application Viscosity (sec)	Recoating* Period (hrs)
<b>Sand the surface with Emery Paper 180 and wipe clean</b>					
<b>Asian Paints Decoprime Wall Primer( E1 or E2)</b> Brush or Spray	<b>0359 or 0360</b>	Mineral Turpentine Oil (for E1) or Water (for E2)	8-10 15-20	30-40 20-25	6-8 hrs
<b>Asian Paints Wall Putty (E0)</b> Putty Knife	<b>1354</b>	Water	Small amounts to improve flowability	N.A.	4-6 hrs
<b>Sand with Emery Paper 180 and wipe clean</b>					
<b>Asian Paints Decoprime Wall Primer( E1 or E2)</b> Brush or Spray	<b>0359 or 0360</b>	Mineral Turpentine Oil (for E1) or Water (for E2)	8-10 15-20	30-40 20-25	6-8 hrs
<b>Sand with Emery Paper 320 and wipe clean</b>					
<b>Asian Paints Tractor Acrylic Distemper (DA) 1st coat</b> Brush, Roller, Spray	<b>0015</b>	Water	55-60 50-55	20-25 25-35	3-4 hrs
<b>Asian Paints Tractor Acrylic Distemper (DA) 2nd coat</b> Brush, Roller, Spray	<b>0015</b>	Water	55-60 50-55	20-25 25-35	3-4 hrs

**Spray application:** Air assisted spray application at pressure 25 - 30 psi  
\*Recoat period is quoted for 25° C and 50% Relative Humidity, these may vary under different conditions.  
🖌️ Brush 🚫 Spray

TAD\_PRODUCTINFO\_SIZE: 8.25" X 11.75" \_24/09/03\_FRONT



Tractor Acrylic Distemper

DA

V.No. 110/2003

**Technical Data**

- a) Coverage\*\*:** The coverage on smooth primed masonry surface with the recommended application procedure is:  
1 Coat: 17 - 19 sq mt/kg  
2 Coats: 8 - 11 sq mt/kg
- b) Drying Time:** Surface Dry time ~ 30 minutes
- c) Gloss Levels/Sheen Levels:** Matt
- d) Flash Point**
- (IS 101/1987, Part 1, Sec 6):** Tractor Distemper is a water based paint and not flammable.
- e) Stability of Thinned Paint:** Use within 24 hrs.
- f) Shelf-life:** 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

\*\*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application and surface roughness.

**Precautions**

- a) Kindly refer to the MSDS for Asian Paints Tractor Acrylic Distemper, which gives detailed information on safety measures while handling the paint.
- b) Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water.
- c) Do not inhale or inject. In case of inhalation move to fresh air and seek medical attention if the symptoms persist in both the cases.
- d) Use protective equipment like rubber/ polythene gloves, safety goggles/glasses, face mask while handling the paint.
- e) Do not apply when ambient temperature is less than 10° C or if the temperature might drop to this level within 4 hrs of application.
- f) In high-humidity areas, use of a bio-wash solution is recommended to remove surface fungus growth, fungal spores, mould etc before application of the paint system.
- g) Do not over thin or over extend the brush
- h) Do not thin before addition of Asian Paints Apcolite Universal Stainer for customised shades. Do not add more than 5% of Asian Paints Apcolite Universal Stainer. Tinted paints need thorough shaking immediately after tinter addition as well as before use.

**Pack Sizes & Shade Range**

**Pack size availability:**  
Available in 1 kg, 2 kg, 5 kg, 10 kg, 20 kg

**Shade Range:**  
Shades from Colourworld Fandeck and Snow White.

**Post Application Instructions**

For removing stains, sponge clean with a mild soap solution and wipe clean. Ensure a drying time of 2 weeks from application before cleaning.

**Safety Features**

Non-flammable

**Contact us**

For more information on our products and services, visit us at [www.asianpaints.com](http://www.asianpaints.com), else call **1600-22-5678** (service available in select cities only)  
Please note that this data sheet supersedes any previous versions.



Asian Paints (India) Limited, 6A, Shantinagar, Santacruz (East), Mumbai - 400 055.

TAD\_PRODUCTINFO\_SIZE: 8.25" X 11.75" \_29/10/03\_back