



Tractor Synthetic Distemper

DS

Product Description

Asian Paints Tractor Synthetic Distemper is a water-based, interior wall paint. It is the most popular distemper brand in India and gives walls a finish that is good looking, time-tested, durable and value for money.

Performance Features & Benefits

Asian Paints Tractor Synthetic Distemper gives a uniform matt film, which can be wiped with clean water. Being oil bound, the paint film becomes harder over a period of time, which gives better washability and durability. White can be tinted with Asian Paints Apcolite Universal Stainer to obtain customised shades.

Recommended Usage

Asian Paints Tractor Synthetic Distemper can be applied on various types of plasters, false ceiling, asbestos sheets, concrete etc. It is designed for interiors.

Recommended Application

Apply topcoats of Tractor Synthetic Distemper as follows :

Product	Product Code	Thinner	Dilution % (by vol)	Application Viscosity (sec)	Recoating* Period (hrs)
Sand the surface with Emery Paper 180 and wipe clean					
Asian Paints Decoprime Wall Primer(E1 or E2) Brush or Spray	0359 or 0360	Mineral Turpentine Oil (for E1) or Water (for E2)	8-10 15-20	30-40 20-25	6-8 hrs
Asian Paints Wall Putty (E0) Putty Knife	1354	Water	Small amounts to improve flowability	N.A.	4-6 hrs
Sand with Emery Paper 180 and wipe clean					
Asian Paints Decoprime Wall Primer(E1 or E2) Brush or Spray	0359 or 0360	Mineral Turpentine Oil (for E1) or Water (for E2)	8-10 15-20	30-40 20-25	6-8 hrs
Sand with Emery Paper 320 and wipe clean					
Asian Paints Tractor Synthetic Distemper (DS) 1st coat Brush	0014	Water	50-60	N.A.	6 hrs
Asian Paints Tractor Synthetic Distemper (DS) 2nd coat Brush	0014	Water	50-60	N.A.	6 hrs

*Recoat period is quoted for 25° C and 50% Relative Humidity, these may vary under different conditions.

Brush Spray

TSD_PRODUCTINFO_SIZE: 8.25" X 11.75" _24/09/03_FRONT



Tractor Synthetic Distemper

DS

V NO. 110/2003

Technical Data

- a) Coverage**:** The coverage on smooth primed masonry surface with the recommended application procedure is:
1 Coat: 17 - 19 sq mt/kg
2 Coats: 8 - 11 sq mt/kg
- b) Drying Time:** Surface Dry time ~ 15 minutes
- c) Gloss Levels/Sheen Levels:** Matt - no sheen
- d) Flash Point**
- (IS 101/1987, Part 1, Sec 6):** Asian Paints Tractor Distemper is a water based paint and not flammable.
- e) Stability of Thinned Paint:** Use within 24 hrs.
- f) Shelf-life:** 3 years in original tightly closed containers away from direct sunlight and excessive heat.

**Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application and surface roughness.

Precautions

- a) Kindly refer to the MSDS for Asian Paints Tractor Synthetic Distemper, which gives detailed information on safety measures while handling the paint.
- b) Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water.
- c) Do not inhale or inject. In case of inhalation move to fresh air and seek medical attention if the symptoms persist in both the cases.
- d) Use protective equipment like rubber/ polythene gloves, safety goggles/glasses, face mask while handling the paint.
- e) Do not apply when ambient temperature is less than 10° C or if the temperature might drop to this level within 4 hrs of application.
- f) In high-humidity areas, use of a bio-wash solution is recommended to remove surface fungus growth, fungal spores, mould etc before application of the paint system.
- h) Do not over thin or over extend the brush.
- i) Do not thin before addition of Asian Paints Apcolite Universal Stainer for customised shades. Do not add more than 5% of Asian Paints Apcolite Universal Stainer. Tinted paints need thorough shaking immediately after tinter addition as well as before use.

Pack Sizes & Shade Range

Pack size availability:

Available in 1 kg, 2 kg, 5 kg, 10 kg, 20 kg

Shade Range:

Available in 29 shades and White.



Post Application Instructions

For removing stains, wipe with a mild soap solution followed by wiping with clean water. Ensure a drying time of minimum 4 weeks from application before cleaning.

Safety Features

Non-flammable

Contact us

For more information on our products and services, visit us at www.asianpaints.com, else call **1600-22-5678**

(service available in select cities only)

Please note that this data sheet supersedes any previous versions.



Asian Paints (India) Limited, 6A, Shantinagar, Santacruz (East), Mumbai - 400 055.

TSD_PRODUCTINFO_SIZE: 8.25" X 11.75" _29/10/03_back