

Product Description

Utsav Distemper is a water based finish which does not come off on the hands or clothes like Chuna.

Performance Features & Benefits





Utsav Distemper imparts a durable matt finish, which lasts all year round. It is chalk resistant and does not come off like Chuna. It is therefore ideal for consumers using Chuna. Utsav Distemper gives you a distemper finish at an economical price.

Recommended Usage

Utsav Distemper should be used only on interior surfaces. It can be applied on suitably prepared masonry wall surfaces.

Recommended Application

Apply topcoats of Utsav Distemper as follows :

Product	Product Code	Thinner	Dilution % (by vol)	Application Viscosity (sec)	Recoating* Period (hrs)
Sand the surface with Emery Paper 100 and wipe clean					
Utsav Distemper 1st Coat Brush	0036	Water	 75	 18-22	4-6 hrs
Utsav Distemper 2nd Coat Brush	0036	Water	 75	 18-22	4-6 hrs

*Recoat period is quoted for 25° C and 50% Relative Humidity, these may vary under different conditions.

 Brush

Technical Data

- a) Coverage**:
- On smooth masonry surface by brushing :
1 coat :12-14 sq mtr/ltr
2 coats: 6-7 sq mtr/ltr
- b) Drying Time:
- c) Gloss Levels/Sheen Levels:
- d) Stability of Thinned Paint:
- e) Shelf-life:
- Use within 24 hrs.
1 year from date of manufacture in original tightly closed packets kept away from direct sunlight and excessive heat.

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

Precautions

- a) Kindly refer to the MSDS for Utsav Distemper which gives detailed information on safety measures while handling the paint.
- b) Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire.
- c) Do not apply when ambient temperature is less than 10° C or if the tempertaure might drop to this level within 4 hrs of application.
- d) Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water.
- e) Stir well and strain before use.

Post Application Instructions

NA

Safety Features

Non-flammable

Pack Sizes & Shade Range

Pack size availability:

1 kg polypack

Shade Range:

Currently available in 14 shades.



Contact us



For more information, visit our website at www.asianpaints.com

For feedback /complaints, write to Marketing Manager - Services, or call



1800-209-5678

(service available in select cities only)

Please note that this data sheet supersedes any previous versions.

