

asian paints**PRIMERS**

Any surface that needs painting needs asian paints

Product Information Sheet

WOODORITE PRIMER

Scope

Woodorite primer is specially formulated to protect wood. It has an excellent sealing and filling properties which protects wood from swelling due to absorption of moisture. Woodorite primer penetrates wood fibre and gives excellent adhesion to substrate and also serves as a sound base for the application of undercoats and finishing coats. It also protects the finish coat from exudation of resinous matter oozing out from wood.

Areas of Application

Wood

Technical data

Product Code	:	007
Product Type	:	Wood Primer
Finish Variants	:	Smooth and Matt
Shades	:	Pink, White
Viscosity of supply	:	85 ± 10 secs., at 30°C by Ford Cup B4
Thinner	:	Thinner 101
Recommended application viscosity	:	Brushing : 40 - 45 secs. at 30°C by Ford Cup B4 Spraying : 40 - 45 secs. at 30°C by Ford Cup B4
Method of Application	:	Brush or spray
Covering capacity	:	18 - 20 m ² / ltr. / coat
Drying Time	:	Surface Dry – not more than 30 mts. Hard Dry – overnight
Recoating Period	:	10 - 12 hours This property depends upon the ambient temperature and humidity
Packs Offered	:	500 ml, 1 ltr., 4 ltrs., 20 ltrs.
Storage and Handling		
Storage	:	Store in a cool dry place
Disposal	:	Dispose in land filling and not in drain or any water channel
Specific Gravity	:	1.365 ± 0.2
Flash Point	:	Above 30°C (86°F)

Directions for Use

Ensure that the surface is free from dust, dirt, loose particles and moisture. Where previously painted wood work has been stripped, treat as new wood. One or two coats of Woodorite primer Pink / White is recommended. For best results, it is advisable to give 8 hrs. drying time before application of subsequent coats.

DO NOT OVER THIN
STIR WELL AND STRAIN BEFORE USE

Safety Information

Fire Hazard Class

: FLAMMABLE

Safety Precaution

: Work in a well ventilated place. Wear protective clothing like overalls and gloves.

Amir *17/10/11*

asian paints
(INDIA) LIMITED



"Nirmal", 14th Floor, Nariman Point, Bombay 400 021. INDIA
Phone : 0091-22-202 4544 • 0091-22-202 4517 Fax : (022) 202 8993

Although the facts and suggestions in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly or indirectly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.

Enquiries should be addressed to ASIAN PAINTS office or to :