

# Micro Mist Separator Series AMD


Can separate and remove aerosol state oil mist in compressed air and remove particles such as carbon or dust of more than 0.01 μm.  
Use this product as a pre-filter for compressed air for precision instruments or clean room requiring higher clean air.

Modular connection is possible with AMD150C to 550C.  
(For details, refer to page 61.)



AMD150C to 550C

AMD650/850



Made to Order  
(For details, refer to page 67.)

## Model

Model	AMD150C	AMD250C	AMD350C	AMD450C	AMD550C	AMD650	AMD850
Rated flow (ℓ/min (ANR)) <sup>Note)</sup>	200	500	1000	2000	3700	6000	12000
Port size	1/8, 1/4	1/4, 3/8	3/8, 1/2	1/2, 3/4	3/4, 1	1, 1 1/2	1 1/2, 2
Mass (kg)	0.38	0.55	0.9	1.4	2.1	4.2	10.5

Note) Max. flow at 0.7 MPa.  
Max. flow varies depending on the operating pressure.  
Refer to "Flow Characteristics" (page 29) and "Maximum Air Flow" (page 28).

## Model/Free Standing Type

Model	AMD800	AMD900	AMD1000
Rated flow (ℓ/min (ANR))	8000	24000	40000
Port size	50(2B)JIS 10K FF flange	50(2B), 80(3B), 100(4B)JIS 10K FF flange	100(4B), 150(6B)JIS 10K FF flange
Mass (kg)	100	220	430

## Model/Piping Support Type

Model	AMD801	AMD901
Rated flow (ℓ/min (ANR))	8000	24000
Port size	50(2B)JIS 10K FF flange	50(2B), 80(3B), 100(4B)JIS 10K FF flange
Mass (kg)	50	140

## Specifications

Fluid	Compressed air
Max. operating pressure	1.0 MPa
Min. operating pressure*	0.05 MPa
Proof pressure	1.5 MPa
Ambient and fluid temperature	5 to 60°C
Nominal filtration rating	0.01 μm (Filtration efficiency: 99.9%)
Oil mist density at outlet	Max. 0.1 mg/m <sup>3</sup> (ANR)* (Before saturated with oil, less than 0.01 mg/m <sup>3</sup> (ANR) ≈0.008 ppm)
Element life	2 years (1 year for flange type) or when pressure drop reached 0.1 MPa

\* With auto drain: 0.1 MPa (N.O. type) or 0.15 MPa (N.C. type)  
\* Oil mist density at 30 mg/m<sup>3</sup> (ANR) blown out by compressor.

## Accessory

Applicable model	AMD150C	AMD250C	AMD350C	AMD450C	AMD550C	AMD650	AMD850
Bracket assembly (with 2 mounting screws)	AM-BM101	AM-BM102	AM-BM103	AM-BM104	AM-BM105	BM56	BM57

## ⚠ Caution

Be sure to read this before handling.  
Refer to back pages 1 and 2 for Safety Instructions, "Precautions for Handling Pneumatic Devices" (M-03-E3A) for Common Precautions, and back pages 3 through to 7 for Specific Product Precautions.

## How to Order



### AMD150C to 550C

AMD **550C** - [ ] **10** [ ] [ ] - [ ] - [ ]

**Body size**

150C
250C
350C
450C
550C

**Thread type**

Symbol	Type
Nil	Rc
F	G*1
N	NPT

\*1 Conforms to ISO1179-1.

**Port size**

Symbol	Size	Applicable body size				
		150C	250C	350C	450C	550C
01	1/8	●				
02	1/4	●	●			
03	3/8		●	●		
04	1/2			●	●	
06	3/4				●	●
10	1					●

**Accessory**

Symbol	Description
Nil	—
B	Bracket *2

\*2 Bracket is included, (but not assembled).

**Made to Order**

("How to Order" and the applicable models are different from those shown on this page. Be sure to refer to "Made to Order".)

Symbol	Description	Page for details
Nil	—	—
X6	With differential pressure gauge (GD40-2-01)	P.68
X15	With IN-OUT flange	P.69
X17	With differential pressure gauge (GD40-2-01) and IN-OUT flange	P.69
X26	N.C., N.O. auto drain, drain piping type	P.70

**Option \*3**

Symbol	Description
Nil	—
F	Rubber material: Fluororubber
H	For medium air pressure (1.6 MPa)
J	Drain guide 1/4 female thread *4
R	IN-OUT reversal direction
S	With differential pressure switch (125 VAC, 30 VDC) *5, (Note)
U	With differential pressure switch (30 VDC) *5, (Note)
T	With element service indicator
V	Degreasing wash, *6 white vaseline

\*4 Drain piping and piping for a stop valve such as ball valve are required.  
 \*5 Differential pressure gauge is included, (but not assembled).  
 \*6 Only body/housing is degreasing washed.  
 Note) Order "U" if conformity to the EU directive is required.

### Auto Drain Specifications/Option Combinations

○ : Available    □ : Not available  
 ○, △ : Plural options cannot be selected.  
 (i.e. Combinations such as C-FV, D-FHV, J-ST are not possible.)

Symbol	F	H	R	S	U	T	V
Auto drain specifications	○	○	○	○	○	○	○
Nil	○	○	○	○	○	○	○
C	△	□	○	○	○	○	△
D	○	△	○	○	○	○	△
J	○	○	○	○	○	○	○

**Auto drain \*3**

Symbol	Description
Nil	Drain cock (Without auto drain)
C	N.C. auto drain
D	N.O. auto drain

\*3 Refer to "Auto Drain Specifications/Option Combinations".

## Options

**Symbol F: Rubber material: Fluororubber**

Fluororubber is used for the parts such as O-ring and gasket.

**Symbol H: For medium air pressure (1.6 MPa)**

Can be used up to 1.6 MPa at maximum.

**Symbol J: Drain guide 1/4 female threaded**

Can be piped to the drain exhaust port.

**Symbol R: IN-OUT reversal direction**

Air flow in the separator is changed to right to left. (Air flow direction of the standard: Left to right.)

**Symbol S: With differential pressure switch (with indicator)**

Saturation of the separator can be observed visually or by an electrical signal. (Element life check)

**Symbol U: With differential pressure switch (with indicator)**

Saturation of the separator can be observed visually or by an electrical signal. (Element life check)

**Symbol T: With element service indicator**

Saturation of the separator can be observed visually. (Element life check)

Pressure drop 0.1 MPa

\* The rated contact voltage is different from "U".

Max. contact capacity: 10 VA AC, 10 W DC  
 Rated contact voltage (max. operating current): 125 V AC (0.08 A), 30 V DC (0.33 A)

\* The rated contact voltage is different from "S".

Max. contact capacity: 10 W DC  
 Rated contact voltage (max. operating current): 30 V DC (0.33 A)

**Symbol V: Degreasing wash, white vaseline**

Body/housing is degreasing washed. The lubrication grease for O-ring and gasket is changed to white vaseline.


# Series AMD

**Flow Characteristics/Select the model taking the max. flow capacity into consideration. (—— Element oil saturation --- Initial condition)**




Note) Compressed air over max. flow line in the table below may not meet the specifications of the product.  
It may cause damage to the element.


**AMD150C**




**AMD550C**




**AMD9□0/9□1**




**AMD250C**




**AMD650**




**AMD10□0**




**AMD350C**



**AMD80□/81□**



**AMD450C**



**AMD850**

