



Smart solutions.
Strong relationships.

Crompton Pumps



STAINLESS STEEL SUBMERSIBLE PUMPSETS – 4CSS SERIES

RATING	NO OF STAGES	HP	KW	OUTLET SIZE IN MM	HEAD IN METRES	DISCHARGE IN LPM	
---------------	---------------------	-----------	-----------	--------------------------	-----------------------	-------------------------	--

STAINLESS STEEL SUBMERSIBLE PUMPSETS (WATER FILLED MOTOR)-SUITABLE FOR 100 MM BOREWELL

4CSSF3-0508	8	0.5	0.37	32	48-8	0-64	
4CSSF3-7512	12	0.75	0.55	32	72-12	0-64	
4CSSF3-1016	16	1	0.75	32	96-16	0-64	
4CSSF3-1018	18	1	0.75	32	108-18	0-64	
4CSSF3-1520	20	1.5	1.1	32	120-20	0-64	
4CSSF3-1525	25	1.5	1.1	32	150-25	0-64	
4CSSF3-2028	28	2	1.5	32	168-28	0-64	
4CSSF3-2032	32	2	1.5	32	192-32	0-64	
4CSSF5-0506	6	0.5	0.37	40	36-6	0-100	
4CSSF5-7508	8	0.75	0.55	40	48-8	0-100	
4CSSF5-1010	10	1	0.75	40	60-10	0-100	
4CSSF5-1012	12	1	0.75	40	72-12	0-100	
4CSSF5-1515	15	1.5	1.1	40	90-15	0-100	
4CSSF5-1518	18	1.5	1.1	40	108-18	0-100	
4CSSF5-2020	20	2	1.5	40	120-20	0-100	
4CSSF5-2024	24	2	1.5	40	144-24	0-100	
4CSSF8 - 1006	6	1.0	0.75	50	35.4 - 12	0 - 180	
4CSSF8 - 1510	10	1.5	1.10	50	59 - 20	0 - 180	
4CSSF8 - 2012	12	2.0	1.50	50	70.8 - 24	0 - 180	
4CSSF3-1016(3PH)	16	1	0.75	32	96-16	0-64	
4CSSF3-1018(3PH)	18	1	0.75	32	108-18	0-64	
4CSSF3-1520(3PH)	20	1.5	1.1	32	120-20	0-64	
4CSSF3-1525(3PH)	25	1.5	1.1	32	150-25	0-64	
4CSSF3-2028(3PH)	28	2	1.5	32	168-28	0-64	
4CSSF3-2032(3PH)	32	2	1.5	32	192-32	0-64	
4CSSF5-1010(3PH)	10	1	0.75	40	60-10	0-100	
4CSSF5-1012(3PH)	12	1	0.75	40	72-12	0-100	
4CSSF5-1515(3PH)	15	1.5	1.1	40	90-15	0-100	
4CSSF5-1518(3PH)	18	1.5	1.1	40	108-18	0-100	
4CSSF5-2020(3PH)	20	2	1.5	40	120-20	0-100	
4CSSF5-2024(3PH)	24	2	1.5	40	144-24	0-100	
4CSSF8 - 1006(3PH)	6	1.0	0.75	50	35.4 - 12	0 - 180	
4CSSF8 - 1510(3PH)	10	1.5	1.10	50	59 - 20	0 - 180	
4CSSF8 - 2012(3PH)	12	2.0	1.50	50	70.8 - 24	0 - 180	